



DEEP CYCLE AGM TECHNOLOGY

DEEP CYCLE AGM BATTERY

LDC12-90-G24-DT BCIGROUP 24

FEATURES & BENEFITS

- True deep cycle AGM technology-GREEN SOLUTION
- Over 99.99% virgin lead for grid plate and active material
- Heavy duty grid/paste design for deep cycle application
- Maintenance free, non-spillable, valve-regulated
- Double separator configuration: long cycle life & High energy density and super anti-vibration design
- Low self-discharge for longer shelf life



ELECTRICAL SPECIFICATIONS

Voltage(V)	Capacity (AH)					Reserve Capacity (Min)		
	100HR	20HR	10HR	5HR	3HR	@25A	@56A	@75A
12	93	90	85	77	72	175	65	43


PHYSICAL SPECIFICATIONS

Model	Dimensions (mm/inches)				Weight (kg/lbs)	Terminal Type (Standard)	Case Material
	Length	Width	Height	Total Height			
LDC12-90-G24-DT	260 (10.24)	168 (6.61)	208 (8.19)	232.5 (9.15)	23.8 (52.5)	DT-5/16	ABS

Operating Temperature Range		
Discharge	Charge	Storage
-15°C ~ 50°C (5°F ~ 122°F)	0°C ~ 40°C (32°F ~ 104°F)	-15°C ~ 40°C (5°F ~ 104°F)

LDC12-90-G24-DT


DIMENSIONS




Note: D:Positive 19.5^{+0.3}_{-0.3}, D:Negative 17.9^{+0.3}_{-0.3}; Terminal Torque Values in-lb(Nm):176-203(20-23)

PERFORMANCE CHARACTERISTICS


LEOCH LDC AGM Charging Profile




Relationship of OCV and State Of Charge (25°C, 77°F)



Cycle life In relation to Depth Of Discharge



Self-discharge Characteristic



● LEOCH BATTERY CORP. USA:
19751 Descartes, Foothill Ranch, CA 92610 USA
Tel: 949-588-5853 E-mail: sales@leoch.us



DEEP CYCLE AGM BATTERY